

WiFi INDOOR

La línea de AP WiFi ROUTER, está compuesta por equipos que usan el software RouterOS y sus alcances inalámbricos. Unos trabajan en MIMO y otros en 802.11ac. Sus usos dependen de la potencia de emisión, la capacidad de sus procesadores, y la certificación NEMA de su caja. Los hay para el hogar, y para aplicaciones industriales con Controller.

WiFi PARA ESCRITORIOS 2,4 GHz



hAP lite

- Our lowest cost home wireless AP with dual chain 2.4GHz wireless, powered by USB

mAP 2n

- 2.4GHz micro AP, 400MHz CPU, 64MB RAM, 2xEthernet, PoE out

RB951Ui-2HnD

- 2.4GHz 1000mW AP with five Ethernet ports and PoE output on port 5. It has a 600MHz CPU, 128MB RAM and a USB port.

RB951G-2HnD

- 2.4Ghz 1000mW AP, 5xGigabit Ethernet, USB, 600MHz CPU, 128MB RAM

DUAL FREQUENCY: 2,4GHz & 5,8 GHz

- RB4011

QUADCORE1,4Hz-1GBMRAM- 800mW2,4 GHz, and 1,3W QuadMIMO 802,11ac5,8GHz, 1730Mb capable, 3dBantennas, 10*GB Ports, 1*SFP+, PoE IN, PoE OUT

- HAPac2 RB962UiGS-5HacT2HnT

QCore720MHz-128MRAM- 800mW 2,4GHz and 600 Mw 5,8GHz APac-2*2 MIMO antenna 2/4 dB+ 5* 10/100 Ethernet Ports+ Power Supply. PoE

WiFi PARA CIELO RASO 2,4 GHz



cAP Lite

- Single MIMO 2.4GHz Ceiling AP, 650MHz CPU, 64MB RAM, 70mW, PoE

WAP

- MIMO 2.4GHz Ceiling AP, 650MHz CPU, 64MB RAM, 300mW, IP66, PoE

RB951Ui-2HnD CEALING

- MIMO 2.4GHz 1000mW AP with five Ethernet ports and PoE output on port 5. It has a 600MHz CPU, 128MB RAM and a USB port.

RB951G-2HnD CEALING

- MIMO 2.4Ghz 1000mW AP, 5xGigabit Ethernet, USB, 600MHz, 128MB RAM

WiFi CIELO RASO DUAL FREQUENCY: 2,4GHz & 5,8 GHz

WAPac RBwAPG-5HacT2HnD

- Dual 802,ac & MIMO 2/4 dB antenna, 2.4GHz/5,8GHz Ceiling AP, 720MHz CPU, 64MB RAM, 300mW, IP66, PoE

RB-4011-O

- 1,730MHz AP with QCORE1.4GHz/1GBMRAM- 800mW2,4GHz and 1,3W5,8GHz AP-4*4 MIMO antenna 3dB, SFP*, 10/100 Ethernet Ports+ Power Supply. PoE

WiFi OUTDOOR & LTE

La línea de AP WiFi, OUTDOOR puede usarse como complemento para patios y campus sobre el controller CAPS MAN. También puede usarse sobre TDMA para construir redes de Telecomunicaciones Punto Multipunto en frecuencia 2.4GHz

WIFI PARA EXTERIORES SINGLE CHAIN



GrooveA 52HPn

- 2.4Ghz/5Ghz AP/Backbone/CPE, 500mW TX, N-male connector, includes 2.4Ghz/5GHz 6dBi Omni Antenna

Metal 2SHPn

- 2.4Ghz Integrated AP/Backbone/CPE, 1600 mW TX power, N-male connector, 6dBi Omni antenna

DUAL CHAIN/ DUAL FREQUENCY 2,4 GHZ & 5.8 GHZ

WAP ac

- Dual 802,ac & MIMO 2/4 dB antenna, 2.4GHz/5,8GHz Ceiling AP, 600MHz CPU, 64MB RAM, 300mW, IP66, PoE

HAP ac OUT

- 2.4Ghz and 5,8 GHz Integrated AP/Backbone/CPE, 1000 mW TX power, N-male connector. 720MHz/128MRAM.

RB-4011-O

- 1,700MHz AP with QCORE1.4GHz/1GBRAMRAM- 800mW2.4GHz and 1,3W5,8GHz AP-4*4 MIMO antenna 3dB, SFP*, 10/100 Ethernet Ports+ Power Supply. PoE

WIFI PARA EXTERIORES DUAL CHAIN



RB-M11-24

- Hot Spot AP Dual Core 880MHz/256MRAM. 500mW Dual chain, Gigabit Ethernet

BaseBox 2

- 2.4Ghz integrated AP/Backbone/CPE, 2xRPSMA connectors, 1000mW TX power, miniPCI-e slot, Gigabit Ethernet

AP-24-15-90

- 2.4Ghz IP66 AP, 1,000mW dual-chain, 15dB 90 degrees sector antenna, Gigabit Ethernet

EQUIPOS PARA BANDA CELULAR

WAP LTE

- LTE/3G and MIMO 2.4GHz AP, 600MHz CPU, 64MB RAM, 300mW, IP66, PoE

RB-M11G

- LTE/WiFi Integrated AP/Router, 1000 mW TX power, N-male connector. Dual Core 880MHz/256MRAM.